Dry Material

EHK016
Dry Bulk Discharge



Application
- For medium duty suction and discharge of dry bulk materials, sand, gravel and dry cement where high electrical resistance is needed

Markets
- Construction
- Cement
- Swimming pool

Construction
Tube Abrasion resistant static dissipating natural rubber

Reinforcement High-tensile synthetic textile with anti-static copper wire

Cover Abrasion, ozone, and weather resistant synthetic rubber

Color Black

Abrasion loss value acc. DIN53516 ≤60mm^3

Operating temperature
-40°C to +70°C
(-40°F to +158°F)

Packaging
100 ft
Coil on Pallet

-160 Straight 20 ft

Order Fulfillment
Made to Order

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	kg/m	lbs/ft	mtr	ft
EHK016-16	25.4	1.00	37.0	1.46	10.0	145	30.0	435	0.62	0.42	30.5	100
EHK016-20	31.8	1.25	44.0	1.73	10.0	145	30.0	435	0.82	0.55	30.5	100
EHK016-24	38.1	1.50	50.0	1.97	10.0	145	30.0	435	0.95	0.64	30.5	100
EHK016-28	44.5	1.75	58.0	2.28	10.0	145	30.0	435	1.27	0.85	30.5	100
EHK016-32	50.8	2.00	64.5	2.54	10.0	145	30.0	435	1.42	0.95	30.5	100
EHK016-40	63.5	2.50	77.0	3.03	10.0	145	30.0	435	1.73	1.16	30.5	100
EHK016-48	76.2	3.00	90.0	3.54	10.0	145	30.0	435	2.09	1.41	30.5	100
EHK016-56	90.0	3.50	104.0	4.09	10.0	145	30.0	435	2.56	1.72	30.5	100
EHK016-64	101.6	4.00	118.0	4.65	10.0	145	30.0	435	3.25	2.18	30.5	100
EHK016-80	127.0	5.00	146.0	5.75	10.0	145	30.0	435	4.84	3.25	30.5	100
EHK016-96	152.4	6.00	172.0	6.77	10.0	145	30.0	435	6.00	4.03	30.5	100
EHK016-128	203.2	8.00	225.0	8.86	10.0	145	30.0	435	8.71	5.86	30.5	100
EHK016-160	254.0	10.00	276.0	10.87	10.0	145	30.0	435	11.40	7.66	6.1	20

Type of couplings
- Cam and groove
- Combination nipple

Contact coupling manufacturer for attachment procedure and other coupling recommendations